

FLY-98V

iNetVu[®]
by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu[®] FLY-98V Flyaway Antenna is a 98 cm satellite antenna system which is a highly portable, self-pointing, auto-acquire unit that is configurable with the iNetVu[®] 7710 Controller providing fast satellite acquisition within minutes, anytime anywhere. It can be assembled in 10 minutes by one person.

“Compliant for use on ExedeSM Ka Service by ViaSat and on KA-SAT NEWSPOTTER NEWSGATHERING service by Eutelsat”



Features

- One-Piece, high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10lbs) Ka transceiver
- Designed to work with the iNetVu[®] 7710 Controller
- Works seamlessly with the world's emerging commercial ViaSat /KA-SAT satellite Surfbeam II/PRO Auto-acquire modems
- Auto beam select on KA-SAT Tooway services
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires Ka-band satellite within 2 minutes
- Field upgradable to Ku-band
- Captive hardware / Fasteners
- 10 minute assembly by one person, no tools required
- Compact packaging; 3 ruggedized cases
- Supports Skyware Global 98 cm Ka antenna
- Standard 2 year warranty

Application Versatility

If you operate in Ka-band, the FLY-98V system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. This next generation Flyaway Ka terminal delivers affordable broadband Internet services (High-speed access, Video & Voice over IP, file transfer, e-mail or web browsing). Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

C-COM
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)
www.c-comsat.com

Specifications are subject to change

Feb 2017

FLY-98V

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	98 cm Elliptical Antenna, offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass ± 2° Tilt sensor ± 0.1°
Azimuth	± 175°
Elevation	0 - 90°
Polarization	Circular, Auto-switching
Elevation Deploy Speed	Variable, 3°/sec typ.
Azimuth Deploy Speed	Variable 3°/sec typ.
Peaking Speed	0.1°/sec

Environmental

Wind loading	
Operational (no ballast)	50 km/h (30 mph)
Operational (with ballast)	72 km/h (45 mph)
Temperature	
Operational	-30° to 60° C (-22° to 140° F)
Survival	-40° to 65° C (-40° to 149° F)
Water Ingress Rating	IP-66

Electrical

Rx & Tx Cable	Single IFL, RG6 cable - 10 m (33 ft)	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	Receive	Transmit
Frequency (GHz)	18.30 - 20.20	28.10 - 30.00
Feed Interface (Circular)	RG6	RG6
Midband Gain (+0.2 dBi)	43.50 @19.75 GHz	46.60 @29.75 GHz
Antenna Noise Temp. (K)	30° EL= 62 Max.	
Sidelobe Envelope Co-Pol (dBi)		
100λ / D < Ø < 20°	29 - 25 Log Ø	
20° < Ø < 26.3°	-3.5	
26.3° < Ø < 48°	32-25 Log Ø	
48° < Ø < 180°	-10 (typical)	
VSWR	1.3:1	

RF Interface

Radio Mounting	Feed Arm
Coaxial	RG6U F Type to tripod base

Physical

Case 1: Reflector	L: 109 cm (43") H: 29 cm (11.5")	W: 109 cm (43") 28.6 Kg (63 lbs)
Case 2: Tripod/Feed arm	L: 122 cm (48") H: 28cm (11")	W: 58 cm (23") 27.7 Kg (61 lbs)
Case 3: Controller/AZ/EL	L: 44.5 cm (17.5") H: 38 cm (15.5")	W: 80 cm (31.5") 34 Kg (75 lbs)

Motors

Electrical Interface	24VDC	8 Amp (Max.)
----------------------	-------	--------------

Shipping Weights & Dimensions*

Skid: 132 cm x 137 cm x 121.9 cm (52" x 54" x 48") 23.1 Kg (51lbs)
Total weight of system in cases: 90.3 Kg (199 lbs)
Total weight of system in cases on skid: 113.4 Kg (250 lbs)

*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

